



PATIO FURNITURE SUPPLIES

The do-it-yourselfer's resource

How to Install a Sling in a Brown Jordan Aegean Chair

1. Remove the old sling.

- Remove the sling rail caps and cut the sling down the middle.
- Stand to the side of the chair, and hold the back of the sling with one hand and the seat of the sling with the other. Push down on the sling at the back, and pull the sling at the seat until it is removed from the sling rail.

2. Install the sling in the sling rails.

- Install the sling spline (rod) into the sling pockets leaving an extra inch or two on both ends.
- Sling rails should be attached to the frame. Stand to the side of the chair to install one side of the sling. Start at the top and work the sling down one sling rail to the bottom. Support the top of the sling so it doesn't tear on the end of the sling rail while going through the sling rail.
- Remove wrinkles. Before the sling reaches the bottom, hold it tight against the sling rail at the top and pull on the bottom of the sling to pull out the wrinkles in the curve.
- Remove this sling rail before installing the sling on the other side.
- With the second sling rail still attached, stand to the side and repeat to install the second side of the sling. This sling rail should be attached so the chair can hold the sling rail as you work.

3. Re-attach the sling rail.

Now the sling is installed in both sling rails, and only one sling rail is attached.

- You will need a drill with a bolt head attachment.
- Loosen the bolts half-way on the sling rail that is still attached.

c. Starting with the back bolt where the sling rail is not attached, place the bolt through the arm of the frame, and then place the spacer on the bolt. (The spacer will be between the frame and the sling rail.) Move the sling rail closer to the frame until the bolt threads begin to grab. The bolt should barely reach the frame.

c. When the bolt reaches the sling rail, use the drill and pull the trigger.

d. Repeat with the remaining bolts, and then tighten all bolts completely.

NOTE: The Aegean model uses shorter bolts than most models. It helps to use the Dual Stretcher Bar Tool to stretch the sling rails apart enough to start the bolts

The Dual Stretcher Bar Tool is available for rent on patiofurnituresupplies.com and comes with instructions and photos. Used with a socket and ratchet, this tool easily stretches or squeezes sling rails. Tool rental is \$25.00 plus \$75.00 deposit; deposit is refunded when tool is returned to Patio Furniture Supplies within 30 days of customer's receipt of tool.

4. Finish.

- Turn the chair upright and cut the excess sling spline.
- Replace the sling rail caps.