



How to Install Slings in a Winston Chaise

1. Remove the old sling.

- Remove the sling rail caps and cut the back and seat slings down the middle.
- For the chaise back, pull up both halves of the sling, removing them through the top of the sling rails. For the seat, stand in front, and pull both halves of the sling through the front of the sling rails.
- Remove any support bar that is wedged between the two sling rails. Not all models have support bars.

2. Install the sling in the sling rails for the seat.

- Install the sling spline (rod) into the sling pockets leaving an extra inch or two on both ends.
- Sling rails should be attached to the frame. Stand to the side to install one side of the sling on the chaise seat. Start at the front and work the sling through one sling rail towards the back. Support the sling so it doesn't tear on the end of the sling rail while going through the rail.
- Remove wrinkles. Before the sling reaches the chaise back, hold it tight against the sling rail at the bottom and pull on the top end of the sling to pull out any wrinkles.
- Remove this sling rail before installing the sling on the other side.
- With the second sling rail still attached, stand to the side and repeat to install the second side of the sling. This sling rail should be attached so the chaise can hold the sling rail as you work.

3. Re-attach the sling rail.

- Now the sling is installed in both sling rails of the chaise seat, and only one sling rail is attached.
- Using a blanket to protect the finish, lay the chaise on its side so the sling rail is hanging.
 - Place the bolts into the loose sling rail.
 - Using a drill with a bolt head attachment, press down on the bolt until it reaches the frame. The bolt should barely reach the frame.

d. When the bolt reaches the frame, pull the drill's trigger. Only tighten the bolt half way. Depending on the fabric, it may be necessary to loosen the bolt on the opposite sling rail so the bolt can reach.

e. Repeat with the remaining bolts and tighten all bolts completely. The sling is now installed in the seat.

4. Install the sling in the sling rails for the back.

- Remove the bolts from one side of the chaise back including the bolt holding the sling rail to the frame.
- Remove one sling rail and install the sling into that rail.
- Then install the sling into the sling rail that is still attached to the frame.
- Replace the bottom bolt that holds the sling rail to the chaise frame and tighten completely. This will make the sling tight at the bottom of the chaise back.
- Using a blanket to protect the finish, turn the chaise upside down and press down or pry the support bracket into place between the sling rails, being careful not to scratch the frame. Our Dual Stretcher Bar Tool will help in this step by stretching the top of the sling rails apart and allowing the bracket to pop back into place.
- Line up the bolt holes on the support bracket with the sling rail and replace and tighten all remaining bolts.

NOTE: The Dual Stretcher Bar Tool is available for rent on patiofurnituresupplies.com and comes with instructions and photos. Used with a socket and ratchet, this tool easily stretches or squeezes sling rails. Tool rental is \$25.00 plus \$75.00 deposit; deposit is refunded when tool is returned to Patio Furniture Supplies within 30 days of customer's receipt of tool.

5. Finish.

- Turn the chaise upright and cut the excess sling spline.
- Install the sling rail caps.