

Installing Aegean Chaise Slings

AEGEAN CHAISE

Brown Jordan's procedure for installing Brown Jordan chaise lounge slings applies to many of their models including Aegean.

1. Prepare the chaise for installing the sling.

- Remove the old sling and turn the chaise upside down.
- Remove the two bolts holding the sling rail to the frame in the seat area.
- There are two curved bars, one at the seat and one at the feet. The curved bar at the foot-end requires a block of wood be inserted between the rail and bar so the bar won't be in the way when squeezed.
- On the chaise back, remove the two bolts holding the rectangular back support ring to one sling rail. Leave the support ring attached to the other sling rail.

2. Install the seat of the sling.

This one-piece sling is installed from the hinge to the feet, one side at a time, and then from the hinge to the head, one side at a time.

- Turn the chaise right side up, and use the Dual Stretcher Bar Tool to squeeze the frame near the foot of the chaise. Place a cloth between the tool and the frame to protect the finish.
- From the hinge, insert one side of the sling by pushing the sling pocket into the sling rail.
- Run the hard sling rod (included) into the sling pocket while it's in the sling rail. The sling rod keeps the sling from pulling out of the rail.

NOTE: The sling will hang up while pushing it around the curve at the end of the chaise, but once past the curve, the sling pocket will go all the way to the hinge.

- Repeat on the other side so the sling is completely installed in the seat.

3. Install the back of the sling.

Installing the back is much easier because the sling rails on the back are straight.

- From the hinge, insert one side of the sling by pushing the sling pocket into the sling rail.
- Run the hard sling rod (included) into the sling pocket while it's in the sling rail. The sling rod keeps the sling from pulling out of the rail.
- Repeat on the other side so the sling is completely installed in the back.

4. Re-install the support bars on the seat.

- Turn the chaise upside down.
- Reverse the heads on the Dual Stretcher Bar Tool so they are set to spread. Place a cloth between the tool and the frame to protect the finish. Be sure not to push the tool through the fabric.
- First, place the Dual Stretcher Bar Tool near the bolt in the seat area and stretch the sling rails apart.
- Pop the curved bars at the seat and foot areas back into place. The sling will be very tight.
- Tighten the bolts on the seat.

NOTE: With these bolts tightened, re-assembling the back will be much easier.

5. Re-install the support bars the back.

- With the chaise still upside down, pop the support ring back between the back sling rails
- Using the Dual Stretcher Bar Tool, install the two bolts on the back. Place a cloth between the tool and the frame to protect the finish. Be sure not to push the tool through the fabric.

6. Finish.

Turn the chaise over, re-install the sling rail caps.